

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-L117437-3115-62803002-1  
**Report Reference** E117437-20030826  
**Date** 15-May-2021

**Issued to:** Balluff GmbH  
Schurwaldstrasse 9 Neuhausen a.d.F.  
Germany 73765

**This is to certify that representative samples of** NRKH7 - Proximity Switches Certified for Canada  
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** CSA C22.2 NO. 14, 12th Ed., Issue Date: 2013-03-01

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-L117437-3115-62803002-1  
**Report Reference** E117437-20030826  
**Date** 15-May-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BFB, followed by M18, followed by M, followed by three numeric digits, followed by N or P, followed by additional letters and/or numbers.	Proximity switches
BGL, followed by one to three numeric digits, followed by B, followed by three numeric digits, followed by additional letters and/or numbers.	Proximity switches
BKT, followed by 21, followed by M, followed by three numeric digits, followed by N, P or U, followed by additional letters and/or numbers.	Proximity switches
BLE, followed by 12, 18 or 35,, followed by K, M, or E, followed by two letters beginning with N or P, followed by one to three alphanumeric digits, followed by additional letters and /or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BLS, followed by 12, 18 or 35,, followed by K, M or E, followed by XX, followed by one to three alphanumeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BLT, followed by 21, followed by M, followed by three numeric digits, followed by N, P or U, followed by additional letters and/or numbers.	Proximity switches
BOD, followed by 21, 63 or 66,, followed by M, followed by L, R or K, followed by A, B or I, may be followed by I, followed by two numeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BOS, followed by 12, 18 or 35,, followed by K, M or E, followed by two letters beginning with N or P, followed by 1, followed by one to three alphanumeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BOS, followed by 50, followed by K,, followed by X or letters PA, PO, PS, NA, NO, NS, PU, NU, PI, UU, or G, may be followed by one letter, followed by L, R, P, I, W or K, followed by D, H, V, F, R, K, T, E or S, followed by two numeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BOS, followed by Q08, R01, G18, 08, 12, 18, 21 or 63,, followed by M or E, followed by one or two or three letters beginning with G, N, P, U or X, followed by two letters and two numeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches



Bruce Mahrenholz, Director North American Certification Program

UL LLC




Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-L117437-3115-62803002-1  
**Report Reference** E117437-20030826  
**Date** 15-May-2021

BWL, followed by four numeric digits, followed by one letter, followed by three numeric digits, followed by additional letters and/or numbers.	Proximity switches
Series BOS, followed by 18, followed by M, followed by R, followed by one or two or three letters beginning with G, N, P, U or X, followed by two letters and two numeric digits, followed by additional letters and/or numbers.	Proximity Switches
Series BOS, followed by R254 or R080., followed by K, followed by one to three letters, followed by two letters and two numeric digits, followed by additional letters and/or numbers.	Proximity Switches



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-US-L117437-1115-62803002-1  
**Report Reference** E117437-20030826  
**Date** 15-May-2021

**Issued to:** Balluff GmbH  
Schurwaldstrasse 9 Neuhausen a.d.F.  
Germany 73765

**This is to certify that representative samples of** NRKH - Proximity Switches  
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 508, 18th Ed., Issue Date: 2018-03-30

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-US-L117437-1115-62803002-1  
**Report Reference** E117437-20030826  
**Date** 15-May-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BFB, followed by M18, followed by M, followed by three numeric digits, followed by N or P, followed by additional letters and/or numbers.	Proximity switches
BGL, followed by one to three numeric digits, followed by B, followed by three numeric digits, followed by additional letters and/or numbers.	Proximity switches
BKT, followed by 21, followed by M, followed by three numeric digits, followed by N, P or U, followed by additional letters and/or numbers.	Proximity switches
BLE, followed by 12, 18 or 35,, followed by K, M, or E, followed by two letters beginning with N or P, followed by one to three alphanumeric digits, followed by additional letters and /or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BLS, followed by 12, 18 or 35,, followed by K, M or E, followed by XX, followed by one to three alphanumeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BLT, followed by 21, followed by M, followed by three numeric digits, followed by N, P or U, followed by additional letters and/or numbers.	Proximity switches
BOD, followed by 21, 63 or 66,, followed by M, followed by L, R or K, followed by A, B or I, may be followed by I, followed by two numeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BOS, followed by 12, 18 or 35,, followed by K, M or E, followed by two letters beginning with N or P, followed by 1, followed by one to three alphanumeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BOS, followed by 50, followed by K,, followed by X or letters PA, PO, PS, NA, NO, NS, PU, NU, PI, UU, or G, may be followed by one letter, followed by L, R, P, I, W or K, followed by D, H, V, F, R, K, T, E or S, followed by two numeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches
BOS, followed by Q08, R01, G18, 08, 12, 18, 21 or 63,, followed by M or E, followed by one or two or three letters beginning with G, N, P, U or X, followed by two letters and two numeric digits, followed by additional letters and/or numbers.	AC/DC flanged hydraulic cylinder proximity switches



Bruce Mahrenholz, Director North American Certification Program

UL LLC




Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-US-L117437-1115-62803002-1  
**Report Reference** E117437-20030826  
**Date** 15-May-2021

BWL, followed by four numeric digits, followed by one letter, followed by three numeric digits, followed by additional letters and/or numbers.	Proximity switches
Series BOS, followed by 18, followed by M, followed by R, followed by one or two or three letters beginning with G, N, P, U or X, followed by two letters and two numeric digits, followed by additional letters and/or numbers.	Proximity Switches
Series BOS, followed by R254 or R080,, followed by K, followed by one to three letters, followed by two letters and two numeric digits, followed by additional letters and/or numbers.	Proximity Switches



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

