

Mounting Instructions

1 Installation

The BAM MD-VS-002-0002 is a protective Nylon holder for BVS HS-P families of barcode readers. The holster is designed to offer a robust and handy way to attach the readers to desktops, work-tables, forklift trucks, and other types of supports.



Figure 1: General View

The kit is composed of:

1. A protective Nylon case with bracket mounts on 3 sides
2. A mounting bracket
3. A bracket positioning screw with washer



Figure 2: Assembly Kit

1.1 Use of Cable Ties

The bracket mounts on the sides of the holster make it easy to fix the holder to any surface, including vertical tube-shaped structures like forklift truck supports. This can be easily obtained by using flexible cable ties (not included) instead of the bracket to attach the holder to such supports. Insert cable ties through the bracket mounts sliding them until they can be fastened to the support:



Figure 3: Cable Tie Insertion

1.2 Use of Brackets

BAM MD-VS-002-0002 can be mounted onto a mounting surface by simply inserting and positioning the bracket into the Nylon case bracket mounts on **any one of its three sides**. Bracket positioning and mounting are illustrated in the following steps:



Figure 4: Bracket positioning

Mounting Instructions

1.2.1 Upper surface mounting

Insert the bracket into the bracket mounts until it reaches the position illustrated below. Tighten the positioning screw against the bracket mount surface.



Figure 5: Bracket positioning for upper surface mounting

Affix the holder to the mounting surface using appropriate screws according to the type of mounting surface.



Figure 6: Upper surface mounting

1.2.2 Lower surface mounting

Insert the bracket into the bracket mounts until it reaches the position illustrated below. Tighten the positioning screw against the bracket mount surface.



Figure 7: Bracket positioning for lower surface mounting

Affix the holder to the mounting surface using appropriate screws according to the type of mounting surface.



Figure 8: Lower surface mounting